



TECHNICAL STANDARDS &  
SAFETY AUTHORITY  
14th Floor, Centre Tower  
3300 Bloor Street West  
Toronto, Ontario  
Canada M8X 2X4

Show facsimile of manufacturer's logo or trademark, as it will appear on the fitting, in the space below

"Apollo"

## STATUTORY DECLARATION

### Registration of Fittings

I, CHAD NICOLAY, ENGINEER

(Name and Position, e.g. President, Plant Manager, Chief Engineer)

of CONBRACO INDUSTRIES, INC.

(Name of Manufacturer)

Located at 1418 S. PEARL STREET, PAGELAND, SC 29728

(Plant Address)

(843) 679-6161

(Telephone No.)

(843) 672-1556

(Fax No.)

do solemnly declare that the fittings listed hereunder, which are subject to the **Technical Standards and Safety Act**, Boilers and Pressure Vessels Regulation, comply with all of the requirements of ASME B31.3 or ASME B16.34

(Title of recognized North American Standard)

which specifies the dimensions, materials of construction, pressure/temperature ratings, identification marking the fittings and service;

or are not covered by the provisions of a recognized North American standard and are therefore manufactured to comply with \_\_\_\_\_ as supported by the attached data which identifies the dimensions, material of construction, pressure/temperature ratings and the basis for such ratings, the marking of the fitting for identification and service.

I further declare that the manufacture of these fittings is controlled by a quality system meeting the requirements of ISO 9001:2008 which has been verified by the following authority, TUV RHEINLAND OF NORTH AMERICA

The items covered by this declaration, for which I seek registration, are category C type fittings. In support of this application, the following information and/or test data are attached as follows:

PRODUCT DOCUMENTATION (DRAWINGS & CALCULATIONS), ISO 9001:2008 CERTIFICATE

(drawings, calculations, test reports, etc.)


Declared before me at Pageland, SC in the county of Charleston  
the 18<sup>th</sup> day of January AD-2016

Commissioner for Oaths:

Nancy Strawn  
(Printed name)

Nancy Strawn  
(Signature)

Chad Nicolay  
(Signature of Declarer)



#### FOR OFFICE USE ONLY

To the best of my knowledge and belief, the application meets the requirements of the **Technical Standards and Safety Act**, Boilers and Pressure Vessels Regulation, and CSA Standard B51 and is accepted for registration in Category C

CRN: OC10908.5R8

Registered by: K. Kei

Dated: March 7/16

NOTE: This registration expires on March 7/2026

Technical Standards and Safety Authority      Boilers and Pressure Vessels Safety Council

REGISTERED

CRN: OC10908.5R8

Signed: K. Kei

Date: March 7/16


See 2 sheets of attachments for scope. KK  
3/7/16



Apollo Industrial Ball Valves		Pressure Rating by size (psi)							
Valve Series	Material	Technical File	ASME Standard	3000	2000	1500	1000	800	400
73A	ASTM A105 (C. Steel)				0.25" - 1"	1.25" - 2"			
76	ASTM A351-CF8M (S. Steel)				0.25" - 1"	1.25" - 2"	2.5" - 3"		
76-AR	ASTM A351-CF8M (S. Steel)				0.25" - 1"	1.25" - 2"	2.5" - 3"		
76J	ASTM A995-4A (Duplex)				0.25" - 1"	1.25" - 2"	2.5" - 3"		
76J-AR	ASTM A995-4A (Duplex)				0.25" - 1"	1.25" - 2"	2.5" - 3"		
76K	ASTM A995-6A (Super Duplex)	ES1094	B31.3		0.25" - 1"	1.25" - 2"	2.5" - 3"		
76K-AR	ASTM A995-6A (Super Duplex)				0.25" - 1"	1.25" - 2"	2.5" - 3"		
89	ASTM A216-WCB (C. Steel)				0.25" - 1"	1.25" - 2"	2.5" - 3"		
89AR	ASTM A216-WCB (C. Steel)				0.25" - 1"	1.25" - 2"	2.5" - 3"		
399	ASTM A351-CN7M (Alloy 20)				0.25" - 1"	1.25" - 2"	2.5" - 3"		
489	ASTM A216-WCB (C. Steel)				0.25" - 1"	1.25" - 2"	2.5" - 3"		
74	ASTM A494-CZ100 (Nickel)	ES1335	B31.3					0.50" - 2"	
7A	ASTM A216-WCB (C. Steel)	ES1338	B31.3						0.25" - 2"
76F	ASTM A351-CF8M (S. Steel)						0.25" - 3"		
76FJ	ASTM A995-4A (Duplex)	ES1339	B31.3				0.25" - 3"		
76FK	ASTM A995-6A (Super Duplex)						0.25" - 3"		
83A	ASTM A216-WCB (C. Steel)	ES1400	B31.3			0.25" - 2"			
86A	ASTM A351-CF8M (S. Steel)					0.25" - 2"			
92	ASTM A216-WCB (C. Steel)				0.25" - 1"	1.25" - 2"			
96	ASTM A351-CF8M (S. Steel)				0.25" - 1"	1.25" - 2"			
96J	ASTM A995-4A (Duplex)	ES1575	B31.3		0.25" - 1"	1.25" - 2"			
96K	ASTM A995-6A (Super Duplex)				0.25" - 1"	1.25" - 2"			
7H	ASTM A351-CF8M (S. Steel)	ES1337	B31.3					0.25" - 1"	
76-300	ASTM A351-CF8M (S. Steel)				0.50" - 1"	1.25" - 2"			
76-400	ASTM A351-CF8M (S. Steel)	ES1336	B31.3		0.50" - 1"	1.25" - 2"			
76-600	ASTM A351-CF8M (S. Steel)	ES1576	B31.3					0.25" - 2"	
72	ASTM A105 (C. Steel)	ES1332	B31.3	0.50"-2"					

A-351 CN7M registered for use  
up to 100°F. KE 3/7/16

THIS IS PART OF  
CRN OC109085R8  
Technical Standards & Safety Authority  
Boilers & Pressure Vessels  
Safety Program



Apollo Top Entry Ball Valves - 12" Size*		
Valve Series	Material	ASME Standard
A	A351-CN7M (Alloy 20)	
B	A351-CF3M (S. Steel)	
C	A216-WCB (C. Steel)	
G	A351-CG8M (S. Steel)	
H	A494-CW12MW (HASTELLOY C)	
J	CD3MN (DUPLX 2205) <b>A 351</b>	
K	CD3MWCuN (SUPER DUPLEX 2507) <b>A 995</b>	
L	A352-LCC (C. Steel)	B16.34
M	A494-M35-1 (Monel)	
P	A217-C12 (Alloy Steel)	
R	A351-CN3MN (AL-6XN)	
S	A351-CF8M (S. Steel)	
W	A351-CK3MCuM (254 SMO)	
Y	A494 N-12MV (HASTELLOY B)	

*KK 3/7/16*

\*Additional sizes (1/2" - 10") were included in previous application under CRN OC10908.5R7

*- for classes 150, 300 & 600. KK 3/7/16*

