



345 Carlingview Drive
Toronto, Ontario
CANADA M9W 6N9
Tel.: 416.734.3300
Fax.: 416.231.1626
Toll Free: 1.877.682.8772
www.tssa.org

January 24, 2018

SCOTT ISLIP
ROUND ENGINEERING INC
10 SEGWUN RD
WATERDOWN ON L8B 0K6
CA

Service Request Type.: BPV-National BC
Service Request No.: 2180592
Your Reference No.: EH-CRN-27
Registered to.: ENDRESS + HAUSER CONDUCTA INC

Dear SCOTT ISLIP,

Please find enclosed the original response from BC, registered under the CRN No.: 0F19698.51.

As all jurisdictional fees are handled by the Technical Standards and Safety Authority (TSSA), you do not pay any jurisdictions directly.

Should you have any questions or require further assistance, I will be happy to assist you.
For general enquiries, please contact a Customer Service Advisor at 1.877.682.TSSA (8772) or e-mail customerservices@tssa.org. When contacting TSSA regarding this file, please refer to the Service Request number provided above.

Yours truly,

Tanya Francis
Administrative Assistant_ BPV Engineering
Tel. : 416-734-3423
Fax : 416-231-6183
Email : tfrancis@tssa.org

TECHNICAL STANDARDS & SAFETY AUTHORITY
345 CARLINGVIEW DRIVE
TORONTO ON M9W 6N9

Date: November 17, 2017
Account #: 35231
Journal #: 69338

Attn: TANYA FRANCIS

Re: Application for Design Registration

The design, as detailed in your, TSSA SR# 2180592, for a Fitting is accepted for registration as follows:

Registered To: ENDRESS+HAUSER CONDUCTA CRN: 0F19698.51
INC

Drawing #: Report EH-CRN-27

Drawing Revision: 0

Conditions Of Registration:

Registration of CONDUMAX CLS16D/CLS16, Hygenic Conductivity Sensor per att'd scope sheets (3 pgs).

This design was registered based on a technical review performed by the province of initial registration in accordance with the Association of Chief Inspectors policy on reciprocal recognition of design review.

Reviewer's Notes:

As required by CSA B51 4.2.1, this registration expires on October 03, 2027. This CRN is valid until the expiry date as long as the Manufacturer maintains a valid quality control program verified by an acceptable third-party agency until that date. Should the certification of the quality control program lapse before the expiry date, this registration shall become void.

Contact me if you have any questions. The invoice for registration will be forwarded under separate cover.

SHARON PETERS

boiler.designregistration@technicalsaftybc.ca
Design Administration

cc:

ENDRESS+HAUSER CONDUCTA INC.

4123 LA PALMA AVE.
ANAHEIM, CA
92807, USA

13-Sep-17

SCOPE OF CRN REGISTRATION

PRODUCT DESCRIPTION

Description	Design Standard	End Connections	Drawings	EH TI Document
CONDUMAX CLS16D/CLS16	ASME B31.3, ASME B31.1, ASME BPE, ASME VIII-1 UG-101	1", 1-1/2" and 2" ASME BPE, ISO2852, DIN 3276 Ferrule (Note 1), DN50 Varivent (Note 1), BioControl D50	414105, 414113, 134267-0002, 134267-0003, 134267-0004, 134267-0005	TI00227C/07/EN/15.14

PRESSURE - TEMPERATURE RATINGS

MDMT	MAWP AT 68 F	MAWP AT 248 F	MAWP AT 302 F	NOTES
23F	188 psia	130 psia	87 psia	It is recommended that the sensor be subjected to sterilization at 302F for only a short time (45 minutes approximately)

MATERIALS OF CONSTRUCTION

PROCESS HOUSING MATERIAL (NOTE 2)	SENSOR SHELL MATERIAL	NOTES
STAINLESS STEEL 1.4435 TYPE 316L UNS S31603	POLYPHENYLENE SULFIDE PLASTIC, ASTM A479-316L, STAINLESS STEEL 1.4435 TYPE 316L, UNS S31603, ELASTOMERS	Optional process housing materials may be used. See Note 2.

MANUFACTURING LOCATIONS

Endress+Hauser Conducta 70839 Gerlingen incl. manufacturing sites 04736 Waldheim and 64823 Gross-Umstadt, Germany	Endress+Hauser Conducta 215021 Suzhou, Endress+Hauser Analytical Instruments Suzhou Co. Ltd. P.R. China
Endress+Hauser Conducta 4123 LA Palma Ave., Anaheim, CA 92807, USA	

Note 1) The ASME BPE Ferrule and Varivent connection shall be used with a clamp, however the assembly clamp is not part of this CRN. Pressure-Temperature ratings may be limited by the clamp type used in the joint assembly. The clamp used to complete the joint shall have its own CRN and shall have pressure-temperature ratings the same or higher than the product ratings.

Note 2) The following additional alloys of superior or equivalent properties to those listed above are also included in the scope of registration: Type 304 S.Steel UNS S30400, Type 304L S.Steel UNS S30403, Type 316 S.Steel UNS S31600, Type 316L S.Steel UNS S31603, Alloy 20 UNS N08020, Hastelloy C-276 UNS N10276, Hastelloy C22 UNS N06022, Hastelloy B3 UNS N10676, Monel 400 UNS N04400 (Note Monel 400 limited to 100F max.), Inconel 600 UNS N06600, Inconel 625 UNS N06625, Inconel 825 UNS N08825, Duplex S.Steel UNS S31803, Super Duplex UNS S32750, Super Duplex UNS S32760, Titanium Grade 3 UNS R50550 (Note Titanium limited to 247F max.)

**THIS IS PART OF
CRN OF 19698.5**
Technical Standards & Safety Authority
Boilers & Pressure Vessels
Safety Program
Callan Oct. 3/17

OF 19698.5
Safety AUTHORITY
NOV. 16, 2017
TSBC J# 64338

