9410 - 20 Ave N.W. Edmonton, Alberta, Canada T6N 0A4

Tel: (780) 437-9100 / Fax: (780) 437-7787

June 19, 2020

Attention: Tanya Francis

TECHNICAL STANDARDS & SAFETY AUTHORITY

345 CARLINGVIEW DRIVE TORONTO, ON M9W 6N9

The design submission, tracking number 2020-02871, originally received on June 03, 2020 was surveyed and accepted for registration as follows:

 CRN:
 0F19698.52
 Accepted on: June 19, 2020

 Reg Type:
 RENEWAL
 Expiry Date: May 13, 2030

Drawing No.: SCOPE OF CRN REGISTRATION

Fitting type: CONDUMAX CLS16D/CLS16E/CLS16 HYGIENIC SENSORS

Design registered in the name of : ENDRESS + HAUSER CONDUCTA INC

The registration is conditional on your compliance with the following notes:

- ** The Scope of this Revision include:
- renewing 0F19698.52
- adding ASME B31.1 as the design code
- adding a new sensor type (CLS16E)

As indicated on AB-41 Statutory Declaration form and submitted documentation, the code of construction are ASME B31.3 and ASME B31.1.

- It is our understanding that the fitting(s), included as the scope of this submission, that is(are) subject to the Safety Codes Act shall comply with the requirements of the indicated Standard or Code of Construction on the AB-41 Statutory Declaration as supported by the attached data which identifies the dimensions, materials of construction, press./temp. ratings and the basis for such ratings, and the identification marking of the fittings.
- This registration is valid only for fittings fabricated at the location(s) covered by the QC certificate attached to the accepted AB-41 Statutory Declaration form.
- This registration is valid only until the indicated expiry date and only if the Manufacturer maintains a valid quality management system approved by an acceptable third-party agency until that date.
- Should the approval of the quality management system lapse before the expiry date indicated above, this registration shall become void.

An invoice covering survey and registration fees will be forwarded from our Revenue Accounts.

If you have any question don't hesitate to contact me by phone at (780) 433-0281 ext 3337 or fax (780) 437-7787 or e-mail Dick@absa.ca.

^{**} See Worldwide Locations Appendix-Page 1 of 1 for manufacturing locations

^{**} The BPE ferrule must be used with the assembly clamp, the assembly clamp is not included as part of this registration. The assembly clamp used to complete the joint must have a valid Alberta CRN suitable for the service pressure and temperature



9410 - 20 Ave N.W. Edmonton, Alberta, Canada T6N 0A4 Tel: (780) 437-9100 / Fax: (780) 437-7787

June 19, 2020

Sincerely,

DICK, ASHLING, P. Eng. DOP Cert. No. D00007936

2020-02871 Page 2 of 2





STATUTORY DECLARATION Registration of Fittings

I, <u>LE</u>	ONARD AMBROSINI	, GENERAL MANAGER	In this space, show facsimile of manufacturer's logo or trademark as it will appear on the fitting.		
	(name of applicant)	(position title) (must be in a position	of authority)		
of E	NDRESS+HAUSER		CTD		
14-	A -4 OFF ATTAOUED WOD	(name of manufacturer)	Endress+Hauser 🖽		
locate	d at SEE ATTACHED WOR	LDWIDE LOCATIONS APPENDIX (plant address)			
	lemnly declare that the fittings k one)	s listed hereunder, which are subject to	o the Safety Codes Act		
comply with the requirements of ASME B31.3, ASME B31.1 which specifies the dimensions, (title of recognized North American Standard)					
	materials of construction, p	ressure/temperature ratings and ident	tification marking of the fittings, or		
	are not covered by the prov	isions of a recognized North American	n standard and are therefore manufactured		
	to comply with		as supported by the attached		
	(title of	code of construction or other applicable docume	ent)		
	data which identifies the dir	nensions, materials of construction, pr	essure/temperature ratings and the basis		
	for such ratings, and the ma	arking of the fittings for identification.			
I furth	er declare that the manufacto	ure of these fittings is controlled by a c	quality control program which has been		
verifie	ed by the following authority,	SQS (ISO 9001) as	being suitable for the manufacture of		
these	fittings to the stated standard	d. The fittings covered by this declara	tion, for which I seek registration, are		
CAT	ECORY E				
CAI	EGORY F	(brief description of fittings)			
In sup	port of this application, the fo	ollowing information, calculations and/	or test data are attached:		
·		-			
	AWINGS, CALCULATIONS, F	VEFORTS, SCOPE OF CRIV			
DEC	_ARED before me at(city) in the	of (province or state)		
this	day of	/			
(prin		(Month) (Year) See	attached acknowledgme		
	(a Commissioner of Oaths or I	Notary Public)			
(sign)					
	(a Commissioner of Oaths or I	Notary Public)	(signature of applicant)		
For A	ABSA Office Use Only:		2020-02871		
NOTI			ABSA		
To th	e best of my knowledge and dard B51, Clause 4.2, and is	belief, the application meets the requi	rements of the Safety Codes Act and CSA ACCEPTED: 0F19698.52		
Regis	stration Number:		See acceptance letter for conditions of registration.		
Date	Registered:	Expiry Da	Date: 2020-06-19 By: We In Inch		
	ormation you provide is necessary only ire Equipment Discipline.	y for the administration of the programs as required	by the Alberte Sefety Codes Act and Regulations in the This stamp and signature have been affixed electronically		

This stamp and signature have been affixed electronically to this registered design as required by Section 20(1) of the Pressure Equipment Safety Regulation, in accordance with the Electronic Transactions Act.

CALIFORNIA ALL- PURPOSE CERTIFICATE OF ACKNOWLEDGMENT

A notary public or other officer completing this certificate verifies only the identity of the individual who signed the document to which this certificate is attached, and not the truthfulness, accuracy, or validity of that document

and not the trainfalloce, accuracy, or	validity of that accument:
State of California	}
County of Orange	_ }
On 01/29/2020 before me,	Laurel Boles (Here insert name and title of the officer)
personally appeared Leonard Ambrosi	,
who proved to me on the basis of satis- name(s)(s)are subscribed to the within	factory evidence to be the person(s) whose instrument and acknowledged to me that ner/their authorized capacity(ies), and that by
	nent the person(s), or the entity upon behalf of
I certify under PENALTY OF PERJUR	Y under the laws of the State of California that
the foregoing paragraph is true and co	LAUREL BULES
WITNESS my hand and official seal.	Commission No. 2180169 NOTARY PUBLIC-CALIFORNIA ORANGE COUNTY ORANGE COUNTY
Faire Pale	My Comm. Expires JANUARY 16, 2021
Notary Public Signature (N	Notary Public Seal)
ADDITIONAL OPTIONAL INFORMAT	INSTRUCTIONS FOR COMPLETING THIS FOR
DESCRIPTION OF THE ATTACHED DOCUMENT	This form complies with current California statutes regarding notary w if needed, should be completed and attached to the document. Acknowle from other states may be completed for documents being sent to that sta
Alberta Statutory Declaration	as the wording does not require the California notary to violate Califor
(Title or description of attached document)	State and County information must be the State and County where the st
Registration of Fittings	signer(s) personally appeared before the notary public for acknowledg

CAPACITY CLAIMED BY THE SIGNER ☑ Individual (s) □ Corporate Officer (Title) Partner(s) Attorney-in-Fact Trustee(s) Other

Number of Pages 1 Document Date 01/29/2020

(Title or description of attached document continued)

RM

vording and, edgments ite so long nia notary

- ment.
- Date of notarization must be the date that the signer(s) personally must also be the same date the acknowledgment is completed.
- The notary public must print his or her name as it appears within his or her commission followed by a comma and then your title (notary public).
- Print the name(s) of document signer(s) who personally appear at the time of notarization.
- Indicate the correct singular or plural forms by crossing off incorrect forms (i.e. he/she/they, is /are) or circling the correct forms. Failure to correctly indicate this information may lead to rejection of document recording.
- The notary seal impression must be clear and photographically reproducible. Impression must not cover text or lines. If seal impression smudges, re-seal if a sufficient area permits, otherwise complete a different acknowledgment form.
- Signature of the notary public must match the signature on file with the office of the county clerk.
 - Additional information is not required but could help to ensure this acknowledgment is not misused or attached to a different document.
 - Indicate title or type of attached document, number of pages and date.
 - Indicate the capacity claimed by the signer. If the claimed capacity is a corporate officer, indicate the title (i.e. CEO, CFO, Secretary).
- Securely attach this document to the signed document with a staple.

www.NotaryClasses.com 800-873-9865



WORLDWIDE LOCATIONS APPENDIX – PAGE 1 OF 1

ENDRESS+HAUSER CONDUCTA GMBH & CO. KG LOCATIONS & CERTIFYING AUTHORITIES

(rev. June 17, 2020)

Endress+Hauser Conducta GmbH & Co. KG

Dieselstrasse 24 / Postfach 100 154 70839 Gerlingen Germany ISO 9001 Certified by SQS

Endress+Hauser Conducta GmbH & Co. KG

Siemensstraße 2 64823 Groß-Umstadt Germany ISO 9001 Certified by SQS

Endress+Hauser Conducta Waldheim

Gewerbegebiet Richzenhain Landsberger Straße 28 04736 Waldheim Germany ISO 9001 Certified by SQS

Endress+Hauser Conducta, Inc.

4123 East La Palma Ave, Suite 200 Anaheim, CA 92807 United States of America ISO 9001 Certified by SQS

Endress+Hauser Analytical Instruments (Suzhou) Co., Ltd.

No. 31 JiangTianLiLu Suzhou Industrial Park 215126 People's Republic of China **ISO 9001 Certified by SQS** This stamp and signature have been affixed electronically to this registered design as required by Section 20(1) of the Pressure Equipment Safety Regulation, in accordance with the Electronic Transactions Act.

ENDRESS+HAUSER CONDUCTA INC.

4123 LA PALMA AVE. ANAHEIM, CA 92807, USA

Endress + Hauser 4

ABSA
SAFETY CODES ACT - PROVINCE OF ALBERTA
ACCEPTED: 0F19698.52
See acceptance letter for conditions of registration.
Date: 2020-06-19 By: M. A. Jah

This stamp and signature have been affixed electronically to this registered design as required by Section 20(1) of

the Pressure Equipment Safety Regulation, in accordance

20-Feb-20

Page 1 of 1

SCOPE OF CRN REGISTRATION

PRODUCT DESCRIPTION

Description Design Standard End C		End Connections	Drawings	EH TI Document	
	CONDUMAX	ASME B31.3, ASME	1", 1-1/2" and 2" ASME BPE, ISO2852, DIN	414105, 414113, 134267-0002,	
	CLS16D/CLS16E/	B31.1, ASME BPE,	3276 Ferrule (Note 1), DN50 Varivent (Note	134267-0003, 134267-0004, 134267-	TI00227C/07/EN/15.14
L	CLS16	ASME VIII-1 UG-101	1), BioControl D50	0005	

PRESSURE - TEMPERATURE RATINGS

MDMT	MAWP AT 68 F	MAWP AT 248 F	MAWP AT 302 F	NOTES
23F	188 psia	130 psia	87 psia	It is recommended that the sensor be subjected to sterilization at 302F for only a short time (45 minutes approximately)

MATERIALS OF CONSTRUCTION

PROCESS HOUSING MATERIAL (NOTE 2)	SENSOR SHELL MATERIAL	NOTES
STAINLESS STEEL 1.4435 TYPE 316L UNS S31603	POLYPHENYLENE SULFIDE PLASTIC, ASTM A479-316L, STAINLESS STEEL 1.4435 TYPE 316L, UNS S31603, ELASTOMERS	Optional process housing materials may be used. See Note 2.

Note 1) The ASME BPE Ferrule and Varivent connection shall be used with a clamp, however the assembly clamp is not part of this CRN. Pressure-Temperature ratings may be limited by the clamp type used in the joint assembly. The clamp used to complete the joint shall have its own CRN and shall have pressure-temperature ratings the same or higher than the product ratings.

Note 2) The following additional alloys of superior or equivalent properties to those listed above are also included in the scope of registration: Type 304 S.Steel UNS S30400, Type 304L S.Steel UNS S30403, Type 316 S.Steel UNS S31600, Type 316L S.Steel UNS S31603, Alloy 20 UNS N08020, Hastelloy C-276 UNS N10276, Hastelloy C22 UNS N06022, Hastelloy B3 UNS N10676, Monel 400 UNS N04400 (Note Monel 400 limited to 100F max.), Inconel 600 UNS N06600, Inconel 625 UNS N06625, Inconel 825 UNS N08825, Duplex S.Steel UNS S31803, Super Duplex UNS S32750, Super Duplex UNS S32760, Titanium Grade 3 UNS R50550 (Note Titanium limited to 247F max. for ASME B31.3 service and 173F max. for ASME B31.1 Service.)

Note 3) In accordance with ASME B31.1 para. 123.1.2(D) when this product is manufactured from a ASME B31.1 unlisted material and used under the ASME B31.1 code the facility owner must accept the use of the unlisted material.

Note 4) See Attached List of Endress+Hauser Manufacturing locations applicable to this CRN.