

August 09, 2022

Attention: Cecylia Garbacz
TECHNICAL STANDARDS & SAFETY AUTHORITY
345 CARLINGVIEW DRIVE
TORONTO, ON M9W 6N9

The design submission, tracking number 2022-04217, originally received on July 26, 2022 was surveyed and accepted for registration as follows:

CRN : 0B23984.52 **Accepted on:** August 09, 2022
Reg Type: NEW DESIGN **Expiry Date:** March 19, 2032
Drawing No. : FLANGE MODEL CF-125,CF-150
Fitting type: Flanges 1/2" thru 6", CL 125 & 150
Design registered in the name of : VERYLIKE CO LTD

The registration is conditional on your compliance with the following notes:


As indicated on AB-41 Statutory Declaration Declaration or AB-351 Declaration of Conformity form and submitted documentation, the code of construction is other engineering analysis.

- *It is our understanding that the fitting(s), included as the scope of this submission, that is(are) subject to the Safety Codes Act shall comply with the requirements of the indicated Standard or Code of Construction on the AB-41 Statutory Declaration or AB-351 Declaration of Conformity as supported by the attached data which identifies the dimensions, materials of construction, press./temp. ratings and the basis for such ratings, and the identification marking of the fittings.*
- *This registration is valid only for fittings fabricated at the location(s) covered by the QC certificate attached to the accepted AB-41 Statutory Declaration or AB-351 Declaration of Conformity form.*
- *This registration is valid only until the indicated expiry date and only if the Manufacturer maintains a valid quality management system approved by an acceptable third-party agency until that date.*
- *Should the approval of the quality management system lapse before the expiry date indicated above, this registration shall become void.*

An invoice covering survey and registration fees will be forwarded from our Revenue Accounts.

If you have any question don't hesitate to contact me by phone at (780) 433-0281 ext 3330 or fax (780) 437-7787 or e-mail grynchuk@absa.ca.

Sincerely,



GRYNCHUK, MILLA, P. Eng.
DOP Cert. No. D00005217

**STATUTORY DECLARATION
Registration of Fittings**
Single or Multiple Fitting Designs within one Fitting Category

I, Robbie Hung, General Manager
(name of applicant) (position title) (must be in a position of authority)
of Verylike Co., Ltd
(name of manufacturer)

located at No. 335, Sec. 4, Lu-Ho Rd., Lu-Kang, Changhua, Taiwan
(plant address)

In this space, show facsimile of manufacturer's logo or trademark as it will appear on the fitting.

VERYLIKE

do solemnly declare that the fittings listed hereunder, which are subject to the Safety Codes Act (select only one)

- comply with the requirements of MSS SP-106 which specifies the dimensions, (title of recognized North American Standard) materials of construction, pressure/temperature ratings and identification marking of the fittings, or
- are not covered by the provisions of a recognized North American standard and are therefore manufactured to comply with _____ as supported by the (title of code of construction or other applicable document) attached data which identifies the dimensions, materials of construction, pressure/temperature ratings and the basis for such ratings, and the identification marking of the fittings.

I further declare that the manufacture of these fittings is controlled by a quality control program which has been verified as described in the below Table as being suitable for the manufacturing of these fittings to the stated standard, regulation, code, guideline or other applicable document. The fittings covered by the declaration for which I seek registration are as provided in the Supplementary Sheet(s) attached.

Quality Program Verification and Manufacturing Sites

A copy of the Quality Certificate from each manufacturing site must be included

Item #	Product Description, Model or Series	Quality Program	Scope of Certification	Expiry Date	Verifying Organization	Location(s) Plant Name and address
1.	Flanges	ISO 9001:2015	Manufacture and Sales	October 17, 2024	EUROCERT	Changhua, Taiwan
2.						

Tracking #: _____

In support of this application, the following information, calculations and/or test data are attached:

Scope of CRN, Drawings, Reports

✓ Rodchuk (Signature of the Declarer) ✓ 2021/12/2 (Date)

DECLARED before me at Lu-Kang (city) in the County of Changhua (province, territory, or state)

this 2 day of Dec, 2021 (Month) (Year)

(print) (a Commissioner of Oaths or Notary Public)

(sign) (a Commissioner of Oaths or Notary Public)

(expiry date (mm/dd/yy))

Commissioner of Oaths / Notary Public in and for: (province, territory, or state)

For ABSA Office Use Only:

NOTES:

Registration box containing fields for CRN, Registered Date, Expiry Date, Signature, and a red ABSA stamp with acceptance details.

Tracking #:

見證書

申請人：全好有限公司，公司統一編號：22213442，公司
登記營業地址：彰化縣鹿港鎮頂番里鹿和路四段 335 號。

法定代理人：洪瑞忠，男，身分證字號：N123727471

見證事項：印鑑章

茲證明全好有限公司法定代理人洪瑞忠於二〇二一年十二月十一日在本見證人面前，於本見證書前附英文文件上親自加蓋全好有限公司及法定代理人之印鑑章。

見證人：劉妍孝律師



二〇二一年十二月十一日

Notarial Certificate

Applicant: Verylike CO., Ltd

Government Uniform Invoice number: 22213442

Location: No. 335, Sec. 4, Lu-Ho Rd., Lu-Kang, Changhua, Taiwan
(50543)

Legal representative: Hung Jui Chung, male, ID number: N123727471

Notarization matter: The Seal of the witness

Entrusted agent: Lui Yan Xiao lawyer

This is to certify that the entrusted agent has affixed the seal on the
English documents before the notary public on December 11, 2021.

Entrusted agent: Lui Yan Xiao lawyer

December 11, 2021.

SCOPE OF CRN REGISTRATION

Product Description	Design Code	Size Range	Process Connection	Model	Flange Material	Pressure Class	Pressure-Temperature Ratings	MDMT	Design Report
Cast Copper Alloy Flanges	MSS SP-106	NPS 1/2" thru NPS 6"	Solder Joint Flanged	CF-150	Copper Alloy ASTM B62 UNS No. C83600, ASTM B584 UNS No. C83600	Class 150	225 psig at 150°F	0°F	R-1524 R.0
							220 psig at 175°F		
							210 psig at 200°F		
							205 psig at 225°F		
							195 psig at 250°F		
							190 psig at 275°F		
							180 psig at 300°F		
							165 psig at 350°F		
				150 psig at 406°F					
				CF-125	Copper Alloy ASTM B584 UNS No. C83800, ASTM B584 UNS No. C84400	Class 125	105 psig at 150°F		
							100 psig at 175°F		
							95 psig at 200°F		
							90 psig at 225°F		
							90 psig at 250°F		
							85 psig at 275°F		
							85 psig at 300°F		
							75 psig at 350°F		
				70 psig at 406°F					
				CF-150	Copper Alloy ASTM B584 UNS No. C83800, ASTM B584 UNS No. C84400	Class 150	210 psig at 150°F		
							205 psig at 175°F		
							195 psig at 200°F		
							190 psig at 225°F		
							180 psig at 250°F		
							175 psig at 275°F		
170 psig at 300°F									
150 psig at 350°F									
140 psig at 406°F									

SCOPE OF CRN REGISTRATION CONTINUED

Product Description	Design Code	Size Range	Process Connection	Model	Flange Material	Pressure Class	Pressure-Temperature Ratings	MDMT	Design Report
Cast Copper Alloy Flanges	MSS SP-106	NPS 1/2" thru NPS 3"	Threaded FNPT Flanged	CF-150	Copper Alloy ASTM B62 UNS No. C83600, ASTM B584 UNS No. C83600	Class 150	225 psig at 150°F	0°F	R-1524 R.0
							220 psig at 175°F		
							210 psig at 200°F		
							205 psig at 225°F		
							195 psig at 250°F		
							190 psig at 275°F		
							180 psig at 300°F		
							165 psig at 350°F		
							150 psig at 406°F		
				CF-150	Copper Alloy ASTM B584 UNS No. C83800, ASTM B584 UNS No. C84400	Class 150	210 psig at 150°F		
							205 psig at 175°F		
							195 psig at 200°F		
							190 psig at 225°F		
							180 psig at 250°F		
							175 psig at 275°F		
							170 psig at 300°F		
							150 psig at 350°F		
							140 psig at 406°F		

Note 1: MDMT = Minimum Design Metal Temperature

Note 2: Pressure-temperature ratings are in accordance with MSS SP-106 Table 5 and 6.

Note 3: The ratings given in MSS SP-106 at 0°F to 406°F shall also apply at lower temperatures. Products that are to operate at low temperatures shall conform to the rules of the applicable codes under which they are used.

Note 4: The safe pressure-temperature rating of a solder-joint piping system is dependent, not only on the valve, fitting and tubing strength, but also on the composition of the solder used for the joints. Pressure-temperature limitations for solder joints made with typical commercial solders are given in Table 7 of MSS SP-106. It shall be the responsibility of the user to select a solder composition that is compatible with the service conditions, as well as to assure the adequacy of workmanship employed in making the joints.