



345 Carlingview Drive
Toronto, Ontario M9W 6N9
Tel.: 416.734.3300
Fax: 416.231.1626
Toll Free: 1.877.682.8772

www.tssa.org

January 9, 2025

ROUND ENGINEERING INC
10 SEGWUN RD
WATERDOWN ON L8B 0K6

Workorder Type: Registration - Fitting(Conventional)
Workorder No: 14520005
Your Reference No.: R-2153
Registered to: VERYLIKE CO., LTD.

Dear SCOTT ISLIP,

Technical Standards and Safety Authority (TSSA) is pleased to inform you that your submission has been reviewed and registered as follows:

CRN : 0A24088.5ADD1
Main Design No.: Update of the company logo only with no changes in the Scope of Registration
Expiry Date: Jul 21, 2032

Please be advised that a valid quality control system must be maintained for the fitting registration to remain valid until the expiry date.

Note: The fitting material, dimensions, marking, wall thickness, and tolerances shall strictly be complied with ASME B16.18 and B16.22 standards.

The stamped copy of the approved registration and the invoice are mailed separately (There will be no hard copies for electronic submissions). Should you have any questions or require further assistance, please contact a Customer Service Advisor at 1.877.682.TSSA (8772) or e-mail customerservices@tssa.org. We will be happy to assist you. When contacting TSSA regarding this file, please refer to the Service Request number provided above.

Yours truly,

A handwritten signature in black ink, appearing to read "Zivko Gacevic".

Zivko Gacevic , P. Eng.
Engineer, BPV
Tel. : +1 416-734-3429
Email : zgacevic@tssa.org



Technical Standards and Safety Authority
 345 Carlingview Drive
 Toronto, Ontario M9W 6N9
 www.tssa.org

Show facsimile of manufacturer's logo or trademark, as it will appear on the fitting, in the space below

VERYLIKE
OR **V**

STATUTORY DECLARATION
Registration of Fittings

I, Robbie Hung, General Manager
(Name and Position, e.g. President, Plant Manager, Chief Engineer)

of Verylike Co., Ltd.
(Name of Manufacturer)

Located at No. 335, Sec. 4, Lu-Ho Rd., Lu-Kang, Changhua, Taiwan (50543)
(Plant Address) (Telephone No.) (Fax No.)

do solemnly declare that the fittings listed hereunder, which are subject to the **Technical Standards and Safety Act**, Boilers and Pressure Vessels Regulation, comply with all of the requirements of ASME B16.18, B16.22
(Title of recognized North American Standard)
 which specifies the dimensions, materials of construction, pressure/temperature ratings, identification marking the fittings and service;


or are not covered by the provisions of a recognized North American standard and are therefore manufactured to comply with _____ as supported by the attached data which identifies the dimensions, material of construction, pressure/temperature ratings and the basis for such ratings, the marking of the fitting for identification and service.

I further declare that the manufacture of these fittings is controlled by a quality system meeting the requirements of ISO 9001:2015 which has been verified by the following authority, EUROCERT.

The items covered by this declaration, for which I seek registration, are category A - Pipe Fittings type fittings. In support of this application, the following information and/or test data are attached as follows:

Scope of CRN Registration, Reports, Drawings
(drawings, calculations, test reports, etc.)

Declared before me at Lu-kang in the Counrey of Changhua
 the 5 day of Nov AD 2024.

Commissioner for Oaths: 
(Printed name)

(Signature)

(Signature of Declarer)

FOR OFFICE USE ONLY

To the best of my knowledge and belief, the application meets the requirements of the **Technical Standards and Safety Act**, Boilers and Pressure Vessels Regulation, and CSA Standard B51 and is accepted for registration in Category 'A'.

CRN: _____
 Registered by: _____
 Dated: _____



This Document has been digitally signed and approved. The stamp size has been optimized for 11 x 17 documents.

NOTE: This registration expires on: Jul. 21, 2032

Technical Standards and Safety Authority
 Boilers and Pressure Vessels Safety Program

REGISTERED

C.R.N.: 0A24088.5ADD1

Signed: Jacme Z...

Date: January 9, 2025.

**Information provided in this application is releasable under the Freedom of Information and Privacy Protection Act and may be disclosed upon request.*

見證書

申請人：全好有限公司，公司統一編號：22213442，公司
登記營業地址：彰化縣鹿港鎮頂番里鹿和路四段 335 號。

法定代理人：洪瑞忠，男，身分證字號：N123727471

見證事項：印鑑章

茲證明全好有限公司法定代理人洪瑞忠於二〇二四年
十一月五日在本見證人面前，於本見證書前附英文文
件上親自加蓋全好有限公司及法定代理人之印鑑章。

見證人：劉妍孝律師



二〇二四年十一月五日

Notarial Certificate

Applicant: VERYLIKE CO., LTD

Government Uniform Invoice number: 22213442

Location: No. 335, Sec. 4, Lu-Ho Rd., Lu-Kang, Changhua, Taiwan
(50543)

Legal representative: Hung Jui Chung, male, ID number: N123727471

Notarization matter: The Seal of the witness

Entrusted agent: Lui Yan Xiao lawyer

This is to certify that the entrusted agent has affixed the seal on the
English documents before the notary public on November , 2024

Entrusted agent: Lui Yan Xiao lawyer

November 5 , 2024

VERYLIKE

SCOPE OF CRN REGISTRATION

Product Description	Design Code	Size Range	Process Connection	Pressure-Temperature Ratings, psi (Note 3, 4, 5, 6)				MDMT (Note 1)	Design Report							
				-20°F to 100°F	150°F	200°F	250°F			300°F	350°F	400°F				
Copper Alloy Fittings	ASME B16.18, ASME B16.22	3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4"	Solder Joint, Threaded NPT	Copper Alloy UNS No. C84400 in accordance with ASME B16.18 para. 6, Copper Alloy UNS No. C12200 in accordance with ASME B16.22 para. 6	-20°F	350°F	400°F	R-1504 Rev. 0								
									Standard Water							
									Tube Size							
									3/8	775	660	635	620	610	515	385
									1/2	720	610	585	575	565	480	360
									3/4	580	490	475	465	455	385	290
									1	490	420	400	395	385	325	245
									1-1/4	435	370	355	350	340	290	215
									1-1/2	405	345	330	325	315	270	200
									2	360	305	295	290	280	240	180
2-1/2	335	285	270	265	260	220	165									
3	315	265	255	250	245	210	155									
4	290	245	240	230	225	195	145									
VERYLIKE Item Number Listing																
Item No.	Size	Item No.	Size	Item No.	Size	Item No.	Size	Item No.	Size							
71104	1/2"	71104M	1/2"	71218	1 1/4"	71239	1/2" X 3/8"									
71105	3/4"	71105M	3/4"	71219	1 1/2"	71240	3/4" X 1/2"									
71106	1"	71106M	1"	71221	3/4" X 1/2"	71241	2"									
71107	1 1/4"	71107M	1 1/4"	71224F	1/2"	71243	1 X 1/2"									
71108	1 1/2"	71108M	1 1/2"	71225	3/4"	71245	3/4"									
71109	2"	71109M	2"	71226	1"	71246	1"									
71110	2 1/2"	71110M	2 1/2"	71228	1/2" X 3/8"	71254	1/2"									
71111	3"	71204	1/2"	71224HE	1/2"	71255	3/4"									
71104F	1/2"	71205	3/4"	71231	1 X 3/4	71260	1/2"									
71105F	3/4"	71206	1"	71232	1 1/4"	71305	3/4" X 1/8" X 3/4"									
71106F	1"	71214	1/2"	71234	1/2"	71306	1" X 1/8" X 1"									
71107F	1 1/4"	71215	3/4"	71235	3/4"	71307	1 1/4" X 1/8" X 1 1/4"									
71108F	1 1/2"	71216	1"	71236	1"	71310	3/4"									
71109F	2"	71217	2"	71238	1/2" X 3/4"	71313	3/4" X 1/2" X 1/2"									

VERYLIKE

SCOPE OF CRN REGISTRATION CONTINUED

VERYLIKE Item Number Listing						
Item No.	Size	Item No.	Size	Item No.	Size	Item No.
71314	3/4" X 1/2" X 3/4"	71337	2" X 2" X 1"	71507	1 1/4"	76001
71320	1/2"	71339	1 1/4" X 1 1/4" X 1"	71508	1 1/2"	71467
71322	3/4"	71320WD	1/2"	71509	2"	71468
71323	3/4" X 3/4" X 1/2"	71340	1/2"	71512	4"	71469
71324	1/2" X 1/2" X 3/4"	71342	3/4"	71551	3/4" X 1/2"	72505
71326	1" X 1" X 1/2"	71344	1" X 1/2" X 1"	71604	1/2"	71606W
71327	1" X 1" X 3/4"	71345	1" X 3/4" X 1"	71605	3/4"	71607W
71328	1 1/4" X 1 1/4" X 1/2"	71390	1/2"	71606	1"	71608W
71329	1 1/4" X 1 1/4" X 3/4"	71504	1/2"	71607	1 1/4"	71609W
71335	1 1/2" X 1 1/2" X 1"	71505	3/4"	71608	1 1/2"	
71336	1"	71506	1"	71609	2"	

Note 1: MDMT = Minimum Design Metal Temperature.

Note 2: Alternative material grades in accordance with ASME B16.18 para. 6 and ASME B16.22 para. 6 may be also be supplied.

Note 3: Pressure-temperature ratings of brazed joints are in accordance with ASME B16.18 Table 3.1-1 and ASME B16.22 Table 3.1.1-2 which are shown above. For solder joints the safe pressure-temperature rating of a solder-joint piping system is dependent, not only on the valve, fitting and tubing strength, but also on the composition of the solder used for the joints. Therefore for solder joints the pressure-temperature ratings of the system shall be the lowest of the values shown in ASME B16.18 Table 3.1-1 and ASME B16.22 Table 3.1.1-2 above or that of the solder joint. Pressure-temperature limitations for solder joints made with typical commercial solders are given in Non Mandatory Appendix A of ASME B16.18 and Table I-1 of ASME B16.22. It shall be the responsibility of the user to select a solder composition that is compatible with the service conditions, as well as to assure the adequacy of workmanship employed in making the joints.

Note 4: For low temperature operation the products shall conform to the rules of the applicable codes under which they are used.

Note 5: The internal pressure rating applies to the largest opening of the fitting.

THIS IS PART OF CRN
 0A24088.5ADD1
 Technical Standards and Safety Authority
 Boilers and Pressure Vessels Safety
 Program